

Universal Primer Termo Organika TO-GU

- ready to use
- reduces and balances the absorption of base surfaces
- improves the adhesiveness of the coats applied
- does not contain solvents
- for inside and outside use

Application

Termo Organika TO-GU universal primer is intended for priming and enhancing absorbent and porous base surfaces, such as aerated concrete, ceramic, silicate bricks, cement, cement/lime and gypsum plasters, before painting, plastering, affixing ceramic tiles, applying wallpaper, etc. In the Termo Organika® thermal insulation system, it is applied to prime surfaces before affixing EPS boards.

Preparation of the Surface

Every surface must be compact, smooth, load-bearing, dry, clean and without any films which would reduce adhesiveness (grease, dust, etc.). Surfaces which are very dusty should first be treated with TO-GU universal primer diluted in water in a proportion of 1:1, and then with non-diluted primer.

Do not apply the primer onto strongly moisturised and frozen surfaces.

Instructions for Use

Mix the content of the container thoroughly. TO-GU universal primer may be applied with a brush or a roller. Where more than one layer is applied, then apply the next layer approx. 4 - 6 hours after the application of the previous layer is completed.

The application of plaster or paint can start after the primer is completely dry, i.e. after 24 hours, at the earliest.

Do not use rusted or dirty tools. Rinse off fresh smudges with water. After it dries, the primer can only be removed mechanically. Do not mix the primer with other preparations, plasters, mortars, pigments, additives, etc.

During the work and the drying of the primer, the temperature of the surface and the environment may not be lower than +5°C.

Safety of Use

In case of contact of the product with eyes or skin, rinse them with plenty of water and consult a doctor. Keep away from children.

During work, wear protective clothing and eye protectors.

Note

In addition to the above recommendations, follow good building practice and work-safety rules. The manufacturer warrants the quality of the product but has no influence on the manner, place and conditions of its storage and application. Building work should be done by professionally qualified contractors.

Technical Data

- Temperature of application and of the surface: above +5°C
- Estimated consumption: approx. $0.05 \div 0.2$ l/m² when painting twice (depending on the smoothness and absorbency of the surface).
- Estimated yield: approx. $5.0 \div 20.0$ m²/l when painting twice (depending on the smoothness and absorbency of the surface).
- Drying time: approx. 3 hours (depending on humidity and temperature). Low temperature and high humidity can make this duration longer up by several times.
- Storage: 12 months from date of manufacture, in original, sealed packaging, in dry and cool conditions. Do not store the palettes one on top of another. **Protect against frost.**